

CARBON DIOXIDE (CO₂) TRANSMITTER FOR COLD SPACES

HDU and HDU-N transmitters are designed to detect carbon dioxide concentration and temperature inside the unheated spaces like parking halls.

The CO₂ sensor will become self-calibrated regularly by using patented ABCLogic™ method. Outputs, linear 0-10V signals related to CO₂-concentration and temperature, can be used for demand controlled ventilation in buildings.

HDU-N is like HDU, but with a display. As a factory setting the display is scanning between temperature and CO₂ every 2 seconds. By pressing the S1 button inside the desired display mode can be selected.

By changing the normal cover (and display) to the HDK-C option HDU (HDU-N) will become as a controller.

ABCLogic™ & Calibration

ABCLogic™ is a patented self-calibration technique, that is designed to be used in applications where concentrations will drop to outside conditions (appr. 400 ppm) at least twice in a week period (= an unoccupied building). For applications that do not see periodic ambient conditions, ABCLogic™ can be turned off, but a regular single point calibration of the sensor in 6 -12 months is necessary. Checking and calibration is recommended every 5th year even if ABCLogic™ is on.



Technical data:

Supply	24Vac (15...28V) / 2 VA 24Vdc (15...36V) / 2 W
Ranges	
carbon dioxide	0...2000ppm CO ₂
temperature	-50 ... +50°C
Accuracy	
carbon dioxide CO ₂ , 25°C	± 40 ppm +3% from value (ABCLogic™)
temperature	+/- 0,8°C
Long term stability / year	< 2% FS (ABCLogic™)
Temperature dependence	0.2% FS / °C
Pressure dependence	0.17% from value /mbar
Operating temperature	-30...+50 °C
Outputs	0 -10V < 2 mA
Operating humidity	0...95 % RH (non cond.)
Time constant t63	< 6 min
Warm up time	< 10 min
Housing	PC-plastics, IP54
Dimensions w x h x d	105 x 110 x 46 mm

Wiring

1	24V	supply 24Vac/dc
2	0V	supply and outputs
3	CO ₂	output 0...10V (0...2000ppm CO ₂)
4	°C	output 0...10VDC (-50...+50°C)
5	AO3	controller output

Ordering guide:

Model	Product number	Description
HDU	1135090	CO ₂ transmitter
HDU-N	1135091	CO ₂ transmitter with display
HDK-C	1135052	calibration tool and controller option for HDU and HDK

Products fulfill the requirements of directive 2004/108/EY and are in accordance with the standards EN61000-6-3: 2001 (Emission) and EN61000-6-2: 2001 (Immunity).